

WHAT IS CLAIMED AS NEW AND DESIRED TO BE SECURED BY LETTERS
PATENTS OF THE UNITED STATES IS:

1. A direct current motor, comprising:

a rotor including a rotation shaft and rotor coils;

5 a stator configured to apply a magnetic field to the rotor via magnetic poles of the stator opposing magnetic poles of the rotor;

an electrical parts mounting base board fixed on the rotation shaft such that the rotation shaft perpendicularly intersects the electrical parts mounting base board;

a commutator including a contact electrode part formed with a plane conductive layer pattern and connected to the rotor coils, the contact electrode part being formed on the electrical parts mounting base board; and

a pair of electrode brushes in sliding contact with the contact electrode part of the commutator and configured to supply electric power to the rotor coils through the commutator.

15 2. The direct current motor according to claim 1, further comprising:

a noise suppressing element provided on the electrical parts mounting base board and configured to suppress noise produced in the direct current motor.

3. The direct current motor according to claim 1, wherein respective electrode brushes are split into plural separate portions, and wherein sliding contacts of the separate portions with the contact electrode part of the commutator cause a phase difference due to a shift of rotation angle positions of the sliding contacts of the separate portions relative to the contact electrode part.

20

4. The direct current motor according to claim 1, further comprising:
a support base configured to support the rotation shaft of the rotor,
wherein the electrode brushes include respective external terminals configured to
provide an external connection to the direct current motor, and
5 wherein the electrode brushes and the external terminals of the electrode brushes are
fixed on the support base.

5. The direct current motor according to claim 1, further comprising:
at least one rotation detecting brush in sliding contact with the contact electrode part
of the commutator and configured to detect a signal on the commutator indicative of an
10 operation of the direct current motor.

6. The direct current motor according to claim 5, further comprising:
a support base configured to support the rotation shaft of the rotor,
wherein the electrode brushes include respective external terminals configured to
provide an external connection to the direct current motor,
15 wherein the at least one rotation detecting brush includes a respective external
terminal configured to provide an external connection to the direct current motor, and
wherein the electrode brushes, the at least one rotation detecting brush, the external
terminals of the electrode brushes, and the respective external terminal of the at least one
rotation detecting brush are fixed on the support base.

7. The direct current motor according to claim 5, wherein the electrode brushes are
20 configured to contact the commutator at representative first and second rotation angle

positions 180° apart on the commutator, and wherein the at least one rotation detecting brush is configured to contact the commutator at a third rotation angle position such that an angle formed between the at least one rotation detecting brush and one of the electrode brushes is less than $180^\circ/n$, where n is the number of rotor magnetic poles and n is a natural number of 3 or greater.

8. The direct current motor according to claim 5, further comprising:

a noise suppressing element provided on the electrical parts mounting base board and configured to suppress noise produced in the direct current motor.

9. The direct current motor according to claim 5, wherein respective electrode brushes are split into plural separate portions, and wherein sliding contacts of the separate portions with the contact electrode part of the commutator cause a phase difference due to a shift of rotation angle positions of the sliding contacts of the separate portions relative to the contact electrode part.

10. A direct current motor, comprising:

a rotor including a rotation shaft and rotor coils;

a stator configured to apply a magnetic field to the rotor via magnetic poles of the stator opposing magnetic poles of the rotor;

an electrical parts mounting base board fixed on the rotation shaft such that the rotation shaft perpendicularly intersects the electrical parts mounting base board;

a commutator including a contact electrode part formed with a plane conductive layer pattern and connected to the rotor coils, the contact electrode part being formed on the electrical parts mounting base board; and

a pair of electrode brushes in sliding contact with the contact electrode part of the commutator at respective sliding contact positions of a different distance from an axis of the rotation shaft and configured to supply electric power to the rotor coils through the commutator,

5 wherein the respective sliding contact positions of the electrode brushes with the contact electrode part are shifted in the radial direction.

11. The direct current motor according to Claim 10, further comprising:

at least one rotation detecting brush in sliding contact with the contact electrode part of the commutator at at least one sliding contact position and configured to detect a signal on the commutator indicative of an operation of the direct current motor,

wherein the respective sliding contact positions of the electrode brushes and the at least one sliding contact position of the at least one rotation detecting brush are arranged at a different distance from the axis of the rotation shaft, and are shifted from each other in the radial direction.

15 12. A direct current motor, comprising:

a rotor including a rotation shaft and rotor coils;

means for applying a magnetic field to the rotor;

an electrical parts mounting base board fixed on the rotation shaft such that the rotation shaft perpendicularly intersects to the electrical parts mounting base board;

20 a commutator including a contact electrode part formed with a plane conductive layer pattern and connected to the rotor coils, the contact electrode part being formed on the electrical parts mounting base board; and

means for supplying electric power to the rotor coils through the commutator, the

supplying means being in sliding contact with the contact electrode part of the commutator.

13. The direct current motor according to claim 12, further comprising:

means for suppressing noise produced in the direct current motor,

wherein the suppressing means is provided on the electrical parts mounting base

5 board.

14. The direct current motor according to claim 12, further comprising:

means for supporting the rotation shaft of the rotor; and

means for connecting externally to the supplying means,

wherein the supplying means and the connecting means are fixed on the supporting
10 means.

15. The direct current motor according to claim 12, further comprising:

means for detecting a signal on the commutator indicative of an operation of the
direct current motor, the detecting means being in sliding contact with the contact electrode
part of the commutator.

15 16. The direct current motor according to claim 15, further comprising:

means for supporting the rotation shaft of the rotor;

a first means for connecting externally to the supplying means; and

a second means for connecting externally to the detecting means,

wherein the supplying means, the detecting means, and the first and second
20 connecting means are fixed on the supporting means.

17. The direct current motor according to claim 15, further comprising:
means for suppressing noise produced in the direct current motor,
wherein the suppressing means is provided on the electrical parts mounting base
board.

5

18. A direct current motor comprising:
a rotor including a rotation shaft and rotor coils;
means for applying a magnetic field to the rotor;
an electrical parts mounting base board fixed on the rotation shaft such that the
rotation shaft perpendicularly intersects to the electrical parts mounting base board;
a commutator including a contact electrode part formed with a plane conductive layer
pattern and connected to the rotor coils, the contact electrode part being formed on the
electrical parts mounting base board; and
means for supplying electric power to the rotor coils through the commutator, the
supplying means being in sliding contact with the contact electrode part of the commutator at
15 respective sliding contact positions of a different distance from an axis of the rotation shaft,
wherein the respective sliding contact positions of the supplying means with the
contact electrode part are shifted in the radial direction.

15

20

19. The direct current motor according to claim 18, further comprising:
means for detecting a signal on the commutator indicative of an operation of the
direct current motor, the detecting means being in sliding contact with the contact electrode
20 part of the commutator at at least one sliding contact position,
wherein the respective sliding contact positions of the supplying means and the at
least one sliding contact position of the detecting means are arranged at a different distance

from the axis of the rotation shaft, and are shifted from each other in the radial direction.

20. A method of making a direct current motor with a rotor including a rotation shaft and rotor coils, a stator, an electrical parts mounting base board, a commutator including a contact electrode part, and a pair of electrode brushes, said method comprising the steps of:

5 forming the contact electrode part of the commutator with a plane conductive layer pattern on the electrical parts mounting base board;

 fixing the electrical parts mounting base board on the rotation shaft such that the rotation shaft perpendicularly intersects the electrical parts mounting base board;

 providing the pair of electrode brushes on a support base; and

 assembling the support base onto the electrical parts mounting base board and the rotation shaft such that the electrode brushes are in sliding contact with the contact electrode part of the commutator in the same plane.

21. The method of claim 20, further comprising the step of:
 providing a noise suppressing element on the electrical parts mounting base board.

15 22. The method of claim 20, wherein the providing step includes:
 arranging the pair of electrode brushes such that the electrode brushes are in sliding contact with the contact electrode part of the commutator at respective sliding contact positions of a different distance from an axis of the rotation shaft, and the respective sliding contact positions of the electrode brushes are shifted in the radial direction.

20 23. The method of claim 20, wherein the direct current motor further includes at least one rotation detecting brush,

wherein the providing step provides the pair of electrode brushes and the at least one rotation detecting brush on a support base, and

wherein the assembling step assembles the support base onto the electrical parts mounting base board and the rotation shaft such that the electrode brushes and the at least one rotation detecting brush are in sliding contact with the contact electrode part of the commutator in the same plane.

24. The method of claim 23, further comprising the step of:
providing a noise suppressing element on the electrical parts mounting base board.

25. The method of claim 23, wherein the providing step includes:
arranging the pair of electrode brushes and the at least one rotation detecting brush such that respective sliding contact positions of the electrode brushes and at least one sliding contact position of the at least one rotation detecting brush with the contact electrode part of the commutator are at a different distance from an axis of the rotation shaft, and are shifted from each other in the radial direction,

26. An apparatus having a direct current motor, comprising:
a rotor including a rotation shaft and rotor coils;
a stator configured to apply a magnetic field to the rotor via magnetic poles of the stator opposing magnetic poles of the rotor;
an electrical parts mounting base board fixed on the rotation shaft such that the rotation shaft perpendicularly intersects the electrical parts mounting base board;
a commutator including a contact electrode part formed with a plane conductive layer pattern and connected to the rotor coils, the contact electrode part being formed on the

electrical parts mounting base board; and

a pair of electrode brushes in sliding contact with the contact electrode part of the commutator and configured to supply electric power to the rotor coils through the commutator.

5 27. The apparatus according to claim 26, further comprising:

at least one rotation detecting brush in sliding contact with the contact electrode part of the commutator and configured to detect a signal on the commutator indicative of an operation of the direct current motor.

28. An apparatus having a direct current motor comprising:

a rotor including a rotation shaft and rotor coils;

a stator configured to apply a magnetic field to the rotor via magnetic poles of the stator opposing magnetic poles of the rotor;

an electrical parts mounting base board fixed on the rotation shaft such that the rotation shaft perpendicularly intersects the electrical parts mounting base board;

15 a commutator including a contact electrode part formed with a plane conductive layer pattern and connected to the rotor coils, the contact electrode part being formed on the electrical parts mounting base board; and

a pair of electrode brushes in sliding contact with the contact electrode part of the commutator at respective sliding contact positions of a different distance from an axis of the rotation shaft and configured to supply electric power to the rotor coils through the commutator,

20 wherein the respective sliding contact positions of the electrode brushes with the contact electrode part are shifted in the radial direction.

29. The apparatus according to claim 28, further comprising:
at least one rotation detecting brush in sliding contact with the contact electrode part
of the commutator at at least one sliding contact position and configured to detect a signal on
the commutator indicative of an operation of the direct current motor,
5 wherein the respective sliding contact positions of the electrode brushes and the at
least one sliding contact position of the at least one rotation detecting brush are arranged at a
different distance from the axis of the rotation shaft, and are shifted from each other in the
radial direction.

2001/06/06 17:32